



Pinnacle 27

27" roll laminator

The Pinnacle 27 incorporates superior engineering to deliver the highest level of professional lamination quality and easy and intuitive operation. Incorporating GBC's AccuTherm™ heating technology, the Pinnacle 27 outperforms all other laminators in its class.

GBC's AccuTherm™ heating technology provides the most consistent lamination quality with the highest clarity, even on long runs. And the Pinnacle 27 brings added capabilities by running both Nap-Lam® I and II films up to 3 mil thick.

A fully featured control panel completes the Pinnacle 27 by making operation of the laminator simple. Whether using Nap-Lam® I and II film, school projects, banners, posters and more will be at the top of the class.



Added features

- Fast warm-up time of less than 10 minutes
- Runs both Nap-Lam® I and II films; up to 3 mil thick
- Integrated temperature gauge and footage counter
- Built in horizontal trimmer

Product Number

1701700



Pinnacle 27 film

High quality and crystal clear laminating film insures the finest results.





Pinnacle 27

27" roll laminator

Specifications

Photo quality:	Yes
Warm-up time:	6-9 min.
Speed:	Up to 12' per minute
Temperature control:	Variable for Nap-Lam® I or II film
Cold lamination:	No
Speed control:	Variable (10 settings)
Heating:	2 heat shoes, 2 heated rollers
Throat width:	27"
Footage counter:	Yes
Film thickness:	Up to 3 mil

Ready Indicator:	Yes
Rollers:	2 heated, 2 pull
One Touch Key Pad:	Yes
Reverse switch:	Yes
Auto shut-off:	Yes
Warranty:	1 year
Weight:	105.6 lbs
Dimensions (W x L x H):	35 1/2" x 21" x 14 1/4"
Power requirements:	120V ~ 60Hz 12 amps
Safety:	Safety standard certified  

Specifications are subject to change without notification.

For best results use GBC® high quality laminating film.

Laminating Film

Nap-Lam® I Roll Film – 1 mil to 3 mil

Nap-Lam® II Roll film – 1 mil to 3 mil

Applications

- > Posters
- > Banners
- > Charts
- > Presentations
- > Projects
- > Signs
- > Large photos
- > Crafts