Gfp 800 Series

Professional Dual Heat Laminators

Our most flexible, cost-effective laminator yet.



For finishing professionals who need versatility, quality, and economy in one machine, the **Gfp 800 Series** delivers. Turn out thermal encapsulation with low melt films (1.5-10mil), PSA lamination, and mounting jobs quickly and easily. Operators will spend less time on set-ups and changeovers thanks to swing out supply shafts and film rolls up to 10" in diameter. Two front rewind shafts allow thermal encapsulation of prints from a roll.

Versatile productivity for the bottom line – That's the **Gfp** difference.

- ✓ Two swing out supply shafts
- ✓ Two front unwind shafts
- ➤ Roller diameter 5.25"
- ✓ Web clutch adjustment
- ✓ Variable roller gap 1"
- ✓ Motorized rear rewind option
- ✓ Infinitely variable nip adjustment

- ✓ Independent top/bottom heaters
- ✓ Swing up feed table
- ✓ Dual tension controls
- ✓ Print pressure plate
- ✓ 36" table height output
- ✓ Silicone rollers
- CE Certified



Choose a Gfp Professional Dual Heat Laminator for

Mounting Laminating Encapsulating



Two front unwind shafts for roll-to-roll encapsulation.

Motorized rear rewind for roll-to-roll applications





Front and rear Swing-out Film Shafts

Applications

Signs Banners Trade show displays Point-of-purchase Dry-erase boards Floor graphics Graphic mounting Photo mounting Window graphics Vehicle graphics

Specifications

Laminating Width Roller diameter Roller gap Supply roll diameter Rear rewind Max temperature Film thickness Laminating speed Drive motor Pressure adjustment Roller heating Power supply

Power consumption Net weight with stand **Dimensions** Installation Warranty

847DH

47" 5.25" 1" Max 10" OD **Optional** 266° F 1.5 - 10 mil 0-13 ft/min DC geared motor Dual hand wheels Dual (Top/Bottom) 220v 60Hz Max 4400W 601 lbs. 69" x 34" x 49" Included

Single phase/22 amps 1 year parts and labor

865DH

65"

5.25" 1" Max 10" OD **Optional** 266° F 1.5 - 10 mil 0-13 ft/min DC geared motor Dual hand wheels Dual (Top/Bottom) 220v 60Hz Single phase/22 amps Max 5700W 767 lbs 87" x 34" x 49" Included 1 year parts and labor

