Premier 4 25" Business Laminator

- Variable speed Digital display Built in retractable slitters
- Laminates film up to 10 mils
 2-year parts and labor warranty



The **LEDCO Premier 4** is a mid range laminator designed especially for copy and print shops, sign shops, in-house graphics departments, school supply stores and other general business applications.

Easy To Use

- Simple controls
- Variable speed for laminating thicker or thinner film
- · Automatic side scrap slitting
- · Easy threading and roller cleaning

Great Value

- Laminating protects signs, prints, and other documents, eliminating replacement
- 2-year manufacturer's parts and labor warranty
- Operator manual and toll free telephone support

Reliable

- Our most popular light duty business laminator
- · Made in the USA

FEATURES

- Variable speed operates at lower speeds for thicker films (10 mil) and up to 7 feet per minute for thinner (1.5 mil) films.
- Built in retractable slitters remove side scrap and eliminate hand trimming.
- Swing-away heat shoes make it easy to clean silicon rubber rollers.
- Built in threading aids.
- Simple controls included on a compact control pad with international icons and warning symbols.
- Digital temperature indicator lights up when machine is turned on.
- Reverse switch helps in the event of misfed material.

- Forced air cooling allows laminating with thicker films. Our 3-fan cooling system, the most effective of any machine in its class, helps prevent the warping or rippling which may occur when thicker films are too hot upon exiting a laminator.
- Interchangeable driven silicon rubber rollers.
- Adjustable right and left feed guides.
- Clear safety shield protects operators while allowing them to see their work.
- Spring-loaded rubber rollers provide pre-set laminating pressure.
- Supply roll tension can be easily adjusted by simply turning a tension knob.
- Removable power cord.



Premier 4 25" Business Laminator

OPTIONS

Roll Feed Assembly facilitates laminating long items such as banners. Rolling items up on an empty laminating film roll core and putting the core on the roll feed assembly makes laminating even the longest item relatively easy. The roll feed assembly is especially helpful for those producing digital output such as posters, banners, and prints.

Footage Counter can be set to measure film usage. Specify English or metric measurement.

Dust Cover helps keep your **LEDCO Premier 4** clean while not in use, adding to longevity and low maintenance operation.

Stand

SPECIFICATIONS

SI EEII IE/IIIO/IS	
Laminating width	up to 25 inches
Dimensions	32L x 11H x 14W
Shipping dimensions	34L x 16H x 18W
Weight/shipping weight	75 lbs / 84 lbs
Speed	up to 7 fpm (feet per minute)
Electrical – 110 version	110-125v 15 amps
	1300w 50/60 Hz
Electrical – 220 version	208-240v 6.5 amps
	1300w 50/60 Hz
Maximum film gauge (thickness)	10 mil
Maximum laminating thickness	1/8 inch
Maximum film roll diameter	5.5 inches
Maximum 1.5 mil film capacity	1000 feet
Maximum 3 mil film capacity	500 feet
Laminating roll diameter	1.25 inches
Film core size	1 inch

Specifications subject to change without notice.

- Made in the USA
- 2-year manufacturer's parts and labor warranty
- Toll free telephone support
- CE, NRTL, ETL certified for use in North America and Europe (220 version)



13777 W Laurel Dr • Lake Forest, IL 60045 P: 800.323.4307 • F: 847.996.0610