



# SEAL® 65 EL

## Laminator



The SEAL 65 EL is a high quality, affordably priced wide format cold roll laminator designed for new users to confidently create professionally finished graphics. Built for ease of use, it is ideal for mounting and laminating pressure sensitive graphics up to 65 inches wide. Its durable uniframe construction requires no assembly and minimal maintenance.

Whatever the experience level of the operator, the SEAL 65 EL is easy to use and will deliver high performance jobs for the small to medium sized user. With simplified controls and easy material loading, featuring our unique auto-grip rollers, and flip-up in-feed table for fast webbing, it provides the means to efficiently finish inkjet prints.

Made in the U.S.A. at our ISO certified facility and backed by the most dependable manufacturer in the industry, the 65 EL is perfect for the sign shop who wants to expand their range of applications to include wide format finishing. With its CE and ETL certifications, owners can have peace of mind in the safety and reliability of this machine.

The SEAL 65 EL provides the following features:

#### Optimum performance

- High quality, professional finishing results
- Durable uniframe construction
- Manually adjustable nip to 1" for easy handling of most any substrate
- Fast 14ft/min. production speed
- Best warranty in the industry

#### Ease of use

- Flip up in-feed table for easy webbing
- Auto-grip shafts
- Simple controls
- Minimal maintenance
- Roll feed capable
- Optional autogrip supply shaft storage kit
- Optional roll trough

#### Safety

- ETL listed for US/Canada
- CE approved
- Foot switch for hands free operation
- Safety eyes for increased operator safety

The SEAL 65 EL is ideal for producing a wide variety of display graphics.

Single Sided Lamination



Mounting to Rigid Substrates



Applying Pre-mask



Creating Decals



## Technical Specifications

Maximum Working Width	65" (1651 mm)
Maximum Speed	14' /min. (4.25 m/min.)
Dimensions (H x W x D)	48" x 82.25" x 22" (1219 x 2089 x 559 mm)
Shipping Dimensions	54" x 86" x 25" (1372 x 2184 x 635 mm)
Weight	
Net Weight	345 lbs (156 kg)
Shipping Weight	460 lbs (208.5 kg)
Maximum Roll Diameter	
Unwind	8" (200 mm)
Take Up	6" (150 mm)
Maximum Roll Weight	
Unwind	85 lbs (38.5 kg)
Take Up	35 lbs (15.9 kg)
Maximum Roller Opening	1" (25 mm)
Roller Pressure	3 lbs / in (0.53 N / mm)
Electrical Requirements	
U.S. / Canada	115 VAC, 50/60 Hz, 1A, 115W - NEMA 5-15 Plug
Europe	230 VAC, 50/60Hz, 0.5A, 115W - BS1363 Plug or Continental Europe Plug (Schuko style)
Roller Construction	Two silicone covered steel rollers
SEAL 65 EL Part Number	
115 VAC	65656
230 VAC Europe	65655
Optional Equipment	
Roll Trough - Factory / Field Installed	6501 / 6502
Autogrip Supply Shaft Storage Kit - Factory / Field Installed	5409 / 5410



Ergonomic control panel for ease of use.



Manual nip adjustment with height gauge for precise operation.



Heavy duty rear stabilizing feet.